

INSTRUCTION FOR JUMP STARTING AN ENGINE

WARNING-BATTERIES PRODUCE EXPLOSIVE GASES.

Note-Consult Automobile Owner's Manual and Follow All Instructions

Shield eyes and face from batteries at all times. Be sure vent caps are tight and level. Place a damp cloth over any vent caps on both batteries. Handle cloth carefully- do not allow the cloth to come in contact with eyes, skin or clothing. Be sure vehicles do not touch and both electrical systems are off and the same voltage.

Be careful to avoid moving fan blades.

Check the polarity of battery posts. Positive (+) battery post usually has a larger diameter than negative(-) post.

Determine which post of battery is grounded (connected) to the chassis.

If NEGATIVE POST is grounded, connect clamps in the order shown in the diagram and as described for connecting clamps with a grounded negative post.

1. Connect positive (+) cable to positive (+) terminal of discharged battery wired to starter or solenoid.
2. Connect another end of the positive cable to the positive terminal of the booster battery.
3. Connect second cable (-) to another terminal (-) of the booster battery.
4. Make a final connection on the engine block of the stalled vehicle (not to negative post) away from the battery and stand back.
5. Start the vehicle and remove cables in reverse order of connection by disconnecting engine block connection first.

IF POSITIVE POST is grounded, connect clamps in the order shown in the diagram and as described for connecting clamps with a grounded positive post.

1. Connect negative (-) cable to negative (-) terminal of discharged battery wired to starter or solenoid.
2. Connect another end of the negative cable to the negative terminal of the booster battery.
3. Connect the second cable (+) to another terminal (+) of the booster battery.
4. Make a final connection on the engine block of the stalled vehicle (not to positive post) away from the battery and stand back.
5. Start the vehicle and remove cables in reverse order of connection by

disconnecting engine block connection first.